

DECLARATION OF PERFORMANCE

Thermowood CLADDING

No: **004** DOP: **CPR 06-2013**

1. Unique ID of product: Solid softwood cladding strip
2. Named description: Cladding Profile produced from Thermowood
11 to 44 mm Thickness and 42 to 300 mm Width
3. Intended use (s): for internal or external use as wall panels
4. Manufacturer Name: Prowood Limited
Units 2 & 3 Greenbank Business Park
Swan Lane, Hindley Green
Wigan WN2 4EZ
5. Authorised representative: Not Applicable
6. Assessment and Verification of Constancy of Performance (AVCP) System: System 4
7. Name and identification number of the notified body: N/A
8. European Technical Assessment: N/A
9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	D-s1, d0	EN 14915:2006
Dangerous Substances	The materials in this product do not release any hazardous substances in excess of any European or national requirements	
Density	390 kg/ m3	
Thermal Conductivity	1.1	
Dimensional Stability	Tangential 0.8	
	Radial 1.75	
Biological durability	Class 2/3	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Kelly Short – Director at Wigan on 2nd October 2017